





# DISCHARGE FITTINGS

## ACCESSORIES UP TO MAX. 1800 BAR

08.F.1 – 11/19

For pressure regulating valves 00.05893.0023, 00.05893.0041 to .0049 & 00.05893.0067!

Fittings for mounting at pressure regulating valve connection  
(seal ring 01.03465.0786)

	Discharge fittings for the use of double nipples	Code no.
	<p><b>Fitting</b> to connect press. regulating valve and pump head with one additional pressure outlet (M 48 x 2 with internal seal) at 90°.</p> <p>HDP 20 - HDP 500</p>	<p><b>08.00200.9201</b></p>
	<p><b><u>Optional</u></b></p> <p><b>Manifold</b> with an additional discharge port (M 48 x 2 with internal seal) at 90° and two further connections (1/2" BSP with internal seal) at 180°</p>	<p><b>00.05332.0078</b></p>
	<p><b>Fitting</b> to be mounted between press. regulating valve and pump head with two additional pressure outlets (2 x M 48 x 2 with internal seal) at 90°.</p> <p>HDP 20 - HDP 500</p>	<p><b>08.00200.9202</b></p>
	<p><b>Fitting</b> to connect between press. regulating valve and pump head with two additional pressure outlets (2 x M 48 x 2 with internal seal) at 180°.</p> <p>HDP 20 - HDP 500</p>	<p><b>00.00135.1573</b></p>

**HAMMELMANN®**