

AQUABLAST® FR 1000 V

- Hand-guided surface cleaner designed for universal use.
- Spray bar driven by reaction force of the water jets.
- Wear resistant rotary action with labyrinth seal.
- Pressure control via bypass valve of the hp pump per electrical 4-pole system.
- Four wheel carriage.
- Rotating 4-arm nozzle bar.
- Height adjustable spray pipe.
- Height adjustable working height.
- Chassis with two swivel castors and two fixed castors.
- Spray bar housing with special seal and suction outlets.



TYPICAL APPLICATIONS

- Direct vacuuming allows the use of high pressure water blasting in factories and machine shops without halting production.
- Cleaning landing runways.
- Cleaning and vacuuming of petrol, oil and grease deposits.

CONSTRUCTION INDUSTRY

- Removing and vacuuming of paints, mastics, laitance, adhesion inhibitors, renderings, etc.
- Brightening and vacuuming of thermo-plastic flooring.



Nozzle inserts
design "A", "B" or "M"
- 4 pieces -

TECHNICAL DATA

Operating pressure max.:	1000 bar
Working width:	500 mm
Flow rate max.:	160 l/min
Reaction force max.:	840 N
Speed of rotation max.:	1500 min ⁻¹
Pump power max.:	250 kW
Leakage:	0.5 (+ 1.5) l/min
Nominal diameter:	i/d 6 mm

Length:	1792 mm
Width:	684 mm
Height:	1164 mm

Connection thread:	M 24 x 1.5 DKO-S
Suction connection:	Coupling C

Total weight:	130.6 kg
---------------	----------

	Code no.
AQUABLAST® FR 1000 V	00.00078.0057